Motorola V950 Renegade Phone LCD Screen Replacement

Replace the phone LCD screen on the Motorola V950 Renegade

Written By: xxx

INTRODUCTION

Phone was put through the wash and the LCD screen stop working. A new screen replacement was ordered and installed with careful effort. Tools needed; T6 torg driver and maybe a spudger .


TOOLS:

- T6 Torx Screwdriver (1)
- Spudger (1)

PARTS:


- Motorola V950 Renegade PCMOTV950LCD (1)

Step 1 — LCD Screen




- Turn OFF the Phone before repair and remove the battery. Open flip screen and on the inside screen area Remove Four T6 screws.
- Carefully lift off the metal screen cover.
- Lift out the screen. It is attached at the bottom by a press on connection so use the spudger or pick to carefully pry it loose. There is double sided tape keeping it together with the connector.
- The connector and camera holder are attached to the screen with a ribbion connector, be careful not to damage when lifting out.
- Remove the camera from the holder. This is tricky as the fit is somewhat tight. It only goes back into the holder one way, but try and keep the orientation when inserting into the new part to make it simpler.
- Fit the screen into the frame carefully and press the connector at the bottom to connect the screen to the phone.
- Make sure the screen fits properly onto the flip screen holder. Reinstall the metal frame and screws.
- Sorry that I do not have any pictures ready for this guide, but will try to add later. Order part from: FlexQueen.com US: 760 357-0303

Step 2




- Open flip screen and on the inside screen area Remove Four T6 screws. Carefully lift off the metal screen cover.

Step 3




- Lift out the screen. It is attached at the bottom by a press on connection so use the spudger or pick to carefully pry it loose. There is double sided tape on the bottom connector keeping it in contact with the case. There may be tape also on the top piece above the screen.

Step 4




- The connector and camera holder are attached to the screen with a ribbion connector, be careful not to damage when lifting out.

Step 5




- Remove the camera from the holder. This is tricky as the fit is somewhat tight. It only goes back into the holder one way, but try and keep the orientation when inserting into the new part to make it simpler.

Step 6




- Remove the camera from the holder. This is tricky as the fit is somewhat tight. It only goes back into the holder one way, but try and keep the orientation when inserting into the new part to make it simpler.

Step 7



- Make sure the screen fits properly onto the flip screen holder. Reinstall the metal frame and screws.

Step 8



- Sorry there are not complete file pictures ready for this guide, but may be added later. Once the phone is open it is self evident how to replace even without pictures from above directions. Order part from: FlexQueen.com US: 760 357-0303

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-18 08:26:48 PM.